EUROSIDER®

NTS NITRO MASTER

NITROTHERM® SPRAY system

Patented method and painting devices

Technical Data \ Model		NTS NITRO MASTER Single Tube	
Tensione nominale *Rated volage*	V	230	110
Frequenza *Frequency*	Hz	50	60
Corrente nominale *Rated current*	A	5	10
Potenza assorbita *Input power*	VA	1000	
Peso *Weight*	Kg	115	
	lb	254	
Larghezza *Width*	cm	60	
	in	24	
Profondità *Depth*	cm	45	
	in	18	
Altezza *Height*	cm	147	
	in	58	

Model \ Performance	Compressed Air inlet pressure		Nitrogen outlet production		Air inlet consumption	
	bar g	*psi g*	*Nmc/h*	*cuft/h*	*Nmc/h*	*cuft/h*
NTS NITRO MASTER	6	87	4,5	159,2	7,6	268,7
	7	101,5	5,6	197,0	9,2	326,3
	8	116	6,7	235,9	10,9	384,9
	9	130,5	7,8	275,1	12,6	444,9
	10	145	8,9	315,0	14,3	504,9

Le performance si riferiscono al flusso arricchito in azoto con concentrazione del 92% ± 1%, a 20 °C di temperatura ambiente e pressione atmosferica di 1013 mbar.
L'aria compressa in ingresso deve essere esente da impurità (acqua, olio, particelle solide): si consigliano solo elementi filtranti forniti da Eurosider.
Tutti i dati e le immagini sono comunque puramente indicativi e suscettibili di variazione; le performance variano in base a pressioni e temperature sia di ambiente che di esercizio.

Eurosider si riserva il diritto di apportare modifiche anche senza preavviso.

The performance is reffered to fluid enriched in nitrogen with concentration of 92% ± 1%, at environment temperature of 20 °C and atmospheric pressure of 1013 mbar.
Inlet compressed air must be free from impurities (water, oil, solid particles). We advise to use filter elements supplied by Eurosider.
All the data and images are merely approximate and can be changed; the performance vary in accordance with environment and working process pressure and temperature.

Eurosider reserves a right to make modifications, even without advanced notice.

EUROSIDER®
piazzale Thailandia 6 58100 Grosseto - ITALY ph. +39 0564 425117 fax +39 0564 418833 www.eurosider.com info@eurosider.com